



3 fast charging ports

USB-C® PD 3.0 67W¹ (x2)
USB-A QC 3.0 60W¹ (x1)

GaN technology

Faster charging and greater efficiency

Foldable plug design

Ultra compact



PowerWall 67

67W 3-port GaN wall charger

67W
max. power¹



High performance

The PowerWall 67 by Klip Xtreme is a high-performance 67W GaN wall charger with three ports, combining the latest PD 3.0 and QC 3.0 fast charging technologies. Designed for maximum efficiency and heat dissipation, it powers laptops, iPhones, and other devices up to 5x faster than standard 5W chargers. With GaN technology and an intelligent multiprotection system, the PowerWall 67 offers safe, rapid charging in a compact, travel-friendly design.

Highlights

- Latest PD 3.0 and QC 3.0 fast charging technologies
- GaN semiconductor technology: Faster charging, higher efficiency, best heat dissipation
- Charges laptops and other devices with input power up to 67W¹
- Charges an iPhone 16® and other smartphones up to 5x faster than a standard 5W charger
- LED power status indicator
- Intelligent multiprotection system

Technical Specifications

General information	
MPN	KMC-500
Product type	Triple port GaN wall charger
Input	
Input AC voltage	100-240VAC 50/60Hz 1.7A max.
Output	
Total output	57 W max.
Charging technology	GAN last generation.. PD3.0 & QC3.0 PPS/AFC/SCP/FCP
Charging connector type	2x USB-C® (PD3.0) + USB-A (QC3.0)
USB-C® output (PD67W) C1	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/1.75A, 20V/3.35A. PPS:3.3-21V/3A (67W Max)
USB-C® output (PD67W) C2	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/1.75A, 20V/3.35A. PPS:3.3-21V/3A (67W max.)
USB-A output (QC3.0 60W)	5V/3A, 9V/3A, 12V/3A, 20V/3A (60W max.)
Type C1+C2 (combined)	45W+20W
Type C1+USB-A (combined)	45W+18W
Type C2+USB-A (combined)	45W+18W
Type C1 & (C2+USB-A, combined)	45W+15W
No load input power dissipation	≤0.1W
Full load charging input power dissipation	67W max.
Physical Appearance	
Housing material	PC, zinc alloy
Color	Black
LED indicator	Blue
AC plug type	Foldable
Product dimensions	2 x 2 x 1.2 in
Product weight	3.5 oz
Additional information	
Box content	3-port wall charger, QIG
Standards/certifications	NOM
Operating temperature	32 – 95 °F
Storage temperature	-4 – 176 °F
Relative humidity	10 – 90%
Warranty	1 year (for functional, not appearance issues)

1. 67W and 60W are the max. power outputs of the USB-C® ports and USB-A port respectively when using only one of them. Actual charging output per port may vary when using both simultaneously. It will also depend on each connected device's power demand and enabled charging technology. Scan the QR code and go to the product website for more information.

2. Compatible with laptops and other devices requiring up to 67W PD.

klipxtreme.com

Klip Xtreme® is a registered trademark. All rights reserved. USB Type-C®, USB-C® are registered trademarks of USB Implementers Forum. iPhone® is a trademark of Apple Inc., registered in the U.S. and other countries and regions. All other trademarks and brand names are the property of their respective owners. Any mention of such is intended for identification purposes only, and therefore shall not be construed as a claim to any rights on, endorsement or sponsorship by, or affiliation with, those brands. Made in China.

KMC-500